

Interior Roof kit Assembly Instructions

Congratulations on your interior roof kit. You will really appreciate how it finishes off your gazebo.

Many people order their roof kit with the gazebo which allows us to install the pieces for you. In your case you will be required to place all the pieces in their respective locations. Except for a few parts everything is pre-cut and should fit together well. Everyone assembles their gazebos just a little bit different which will cause you to trim just a few items.

Step 1

Sort out your pieces from the longest to the shortest. There will be equal amounts of each and 1 round center piece.

Step 2

You will be placing the cedar on the bottom side of your rafters completely covering them. Hold the longest cedar board up with the groove side facing the outside of the gazebo and the tongue side facing the center. Place the grooved side against the top sill plate or 2 x 4 at the top of the wall. Look to see if the ends are centered on rafter. If they are not you must trim the board long ways , or rip it from end to end until the edges are close to being centered on the rafter. DO NOT cut the ends as this will make more work for you later. Perform this task all the way around the gazebo.

Step 3

install the next largest piece of cedar and nail with the finishing nails to the rafter. Do this all the way around the gazebo as in step 2. Make sure the tongue and groove fits snugly. These should fit nicely onto the rafter as you have already adjusted the first board to accomplish this. Don't worry about small imperfections along the rafter as a trim board will be installed later .

Step 4

Once a you have installed the last cedar board at the top it is time to place the round center piece. To do so simply hold up to the center and nail it into place with finishing nails provided.

Step 5

starting at the bottom and moving all the way around the gazebo, install the bottom section of the trim. Then measure from this piece to the center and trim to make fit.